

# GMK 5250

CAPACIDADE MÁXIMA: 250t

COMPRIMENTO LANÇA: 13,3 / 70,0m

COMPRIMENTO JIB: 12,0 / 37,0m



PATOLAS INTEIRAMENTE EXTENDIDAS

PATOLAS FRONTAL: EXTENDIDA (260") NÃO EXTENDIDA (LATERAIS E TRÁSERAS)

A	13.3	18.6	23.6	28.5	33.5	38.0	42.3	45.4	48.9	52.4	56.2	60.5	64.6	66.9	70.0
3.0 <sub>m</sub>	2500														
3.0 <sub>m</sub>	165.0	146.0	134.0												
4.0 <sub>m</sub>	140.0	135.0	121.0	101.0	63.0										
5.0 <sub>m</sub>	121.0	121.0	111.0	98.5	75.0	59.0									
6.0 <sub>m</sub>	106.0	107.0	104.0	91.0	75.0	59.0	50.5								
7.0 <sub>m</sub>	94.5	95.0	93.5	84.0	73.0	59.0	50.5	44.0							
8.0 <sub>m</sub>	84.5	85.0	83.5	77.5	68.0	58.5	50.5	44.0	37.0						
9.0 <sub>m</sub>	76.0	77.0	75.0	71.5	63.0	56.0	49.0	44.0	37.0	31.0	18.5				
10.0 <sub>m</sub>	64.5	69.5	68.0	66.5	59.0	53.0	47.5	42.5	37.0	31.0	26.0	21.5			
11.0 <sub>m</sub>		63.5	62.0	62.0	55.0	50.5	45.5	40.5	36.0	31.0	26.0	21.5	18.2		
12.0 <sub>m</sub>		58.0	57.0	57.5	51.5	47.5	43.5	38.5	35.0	31.0	26.0	21.5	18.2	15.9	14.5
13.0 <sub>m</sub>		53.5	52.5	53.0	48.5	45.0	41.5	36.5	33.5	30.5	26.0	21.5	18.2	15.9	14.5
14.0 <sub>m</sub>		47.5	48.0	48.5	45.5	42.5	39.5	34.5	32.0	29.5	26.0	21.5	18.2	15.9	14.5
15.0 <sub>m</sub>		40.5	45.0	44.5	43.0	40.0	38.0	32.5	30.5	28.5	25.5	21.5	18.2	15.9	14.5
16.0 <sub>m</sub>		8.8	42.0	41.0	40.5	38.0	36.5	31.0	29.0	27.5	25.0	21.5	18.2	15.9	14.5
18.0 <sub>m</sub>			36.0	35.5	36.0	34.0	33.5	27.5	26.5	25.5	23.5	20.5	18.1	15.9	14.5
20.0 <sub>m</sub>			27.0	30.5	31.5	30.5	30.5	24.5	24.0	23.5	21.5	19.5	17.3	15.8	14.5
22.0 <sub>m</sub>				27.5	27.0	28.0	28.0	22.5	21.5	21.0	20.0	18.5	16.5	15.3	14.5
24.0 <sub>m</sub>				24.5	23.5	24.5	25.5	20.0	19.3	19.4	18.6	17.4	15.7	14.7	14.4
26.0 <sub>m</sub>					21.0	21.5	22.5	18.3	17.5	17.8	17.0	16.3	14.9	13.8	13.6
28.0 <sub>m</sub>					19.7	18.9	19.8	16.8	16.1	16.4	15.7	15.2	14.2	13.1	12.9
30.0 <sub>m</sub>					14.2	17.2	17.7	15.4	14.7	15.0	14.4	14.1	13.6	12.3	12.1
32.0 <sub>m</sub>						16.1	15.8	14.2	13.6	13.9	13.3	13.2	12.8	11.7	11.4
34.0 <sub>m</sub>						13.1	14.3	13.1	12.5	12.8	12.2	12.2	12.0	11.0	10.8
36.0 <sub>m</sub>							12.9	12.1	11.5	11.9	11.3	11.3	11.2	10.3	9.9
38.0 <sub>m</sub>							11.7	11.2	10.6	10.9	10.4	10.4	10.4	9.8	9.3
40.0 <sub>m</sub>								10.1	9.7	10.0	9.5	9.5	9.6	9.3	8.7
42.0 <sub>m</sub>									9.0	9.4	8.8	8.9	9.0	8.9	8.2
44.0 <sub>m</sub>									8.2	8.7	8.2	8.2	8.4	8.4	7.7
46.0 <sub>m</sub>									5.4	8.1	7.6	7.8	7.9	7.9	7.2
48.0 <sub>m</sub>										7.8	7.0	7.4	7.4	7.4	6.8
50.0 <sub>m</sub>										7.4	6.3	7.0	6.9	6.9	6.3
52.0 <sub>m</sub>											5.8	6.6	6.4	6.5	6.0
54.0 <sub>m</sub>												6.3	6.0	6.1	5.6
56.0 <sub>m</sub>												5.8	5.5	5.6	5.3
58.0 <sub>m</sub>													5.0	5.1	4.9
60.0 <sub>m</sub>														4.6	4.5
62.0 <sub>m</sub>															4.3
64.0 <sub>m</sub>															3.7

A: ALTURA DA LANÇA

B: RAIOS DE OPERAÇÃO